



## PARTYBAG 6 TECHNICAL SPECIFICATIONS

### ACOUSTICAL:

Frequency response (-3dB):	70 Hz ÷ 20000 Hz
Max SPL:	120 dB
Tweeter:	1" piezo (Power handling 50 W RMS)
Woofer:	8" by FaitalPRO® (Power handling 130 W RMS)
Amplifier:	Class D 2x50 W RMS, DSP controlled
Enclosure:	Plywood, with bass-reflex

### INPUT/OUTPUT:

Analog inputs:	Jack 6.3 mm (unbalanced) with selectable MIC/LINE level, 2xRCA
Digital inputs:	MP3/USB Player, <i>Bluetooth</i> ® receiver
Analog outputs:	Jack 6.3 mm (unbalanced)
Jack MIC/LINE sensitivity:	30 mV/300 mV (-32 dBv/- 10 dBv)
RCA sensitivity:	300 mV (-10 dBv)
Maximum input level:	1 V (0 dBv)
Maximum output level:	1 V (0 dBv)

### ELECTRICAL:

USB charging port:	5 V $\equiv$ 500 mA
Battery:	7 cell (25.9 V) Li-Ion 5000 mAh (130 Wh)
Battery range at full volume:	8 hours
Battery range at mid volume:	32 hours
External power supply:	Input 100-240 V $\sim$ 50/60 Hz 1 A, Output 29.4 V $\equiv$ 3A

### MECHANICAL:

Height:	48 cm
Width:	31 cm
Depth:	25 cm
Net weight:	6.2 Kg
Woofer protection:	Metallic grid, black
Backpack internal volume:	7 liters (divided into 3 pockets)
Backpack fabric:	CORDURA®, handcrafted in Italy